

ISUZU

ELF



SAFETY PLUS

SRS
AIRBAG

ASR
ANTI-SLIP REGULATOR

ABS
ANTI-LOCK BRAKING SYSTEM

EBD
ELECTRONIC BRAKE FORCE DISTRIBUTION

 **IMMOBILIZER**

AVAILABLE ON NMR 125 MODEL

4 WHEELER

GVW 4,800kg

GVW 5,100kg

NLR
PRO

NMR
125



EURO 4



FREE
SERVICE CAMPAIGN
 **ISUZU**

Product image for illustration purposes only. Actual product may vary.

SPECIFICATIONS		NLR PRO		NMR125	
MODEL CODE		NLR77UEE	NLR77UHE	NMR85UEH	NMR85UHH
Drive Train		4 x 2			
ENGINE					
Model		4JJ1-TCC		4JJ1-TC	
Type		4-Cylinder Inline, 4 Cycle, Water-Cooled			
		OHV, Turbo with Intercooler		DOHC, V6S Turbo with Intercooler	
Displacement	cc	2,999			
Maximum Output (Gross)	kW (PS) @ rpm	77 (105) @ 3,200		91 (125) @ 2,600	
Maximum Torque	Nm (kgfm) @ rpm	230 @ 1,400-3,400		354 @ 1,500	
Emission Level		Euro 4			
Fuel System		Commonrail Direct Injection			
TRANSMISSION					
Model / No. of Speed		MSB-5S		MYJ-5M	
Gear Ratio		Manual 5-Speed			
	1st	5.016		5.315	
	2nd	2.672		2.908	
	3rd	1.585		1.655	
	4th	1.000		1.000	
	5th	0.770		0.721	
	Reverse	4.783		5.068	
	Final	5.857		4.556	
WEIGHT & CAPACITIES					
Gross Vehicle Weight	kg	4,800		5,100	
Curb Weight	kg	1,920	1,970	2,015	2,065
Front	kg	1,385	1,395	1,465	1,475
Rear	kg	535	575	550	590
Fuel Tank Capacity	l	75	100	75	100
AXLE					
Front	Type	Reverse Elliot, I-Beam			
Front Axle Capacity (Design)	kg	2,900			
Rear	Type	Banjo, Full Floating			
Rear Axle Capacity (Design)	kg	3,600		4,600	
SUSPENSION SYSTEM					
Suspension	Front	Semi Elliptical Alloy Steel Leaf Spring with Double Acting Telescopic Shock Absorber, Stabiliser Bar			
	Rear	Semi Elliptical Alloy Steel Leaf Spring with Double Acting Telescopic Shock Absorber			
TYRES & WHEELS					
Tyres		205/85R16		205/75R17.5	
Wheels		16 x 5.5J-85		17.5 x 5.25-115	
BRAKES					
Service	Type	Hydraulic System with Auto Adjusting Front and Rear Drum Brakes			
		Dual Circuit, Vacuum Assistance and Anti-Lock Brake System (ABS) with Electronic Brake Force Distribution (EBD)			
Parking Brake Type		Transmission Mounted, Mechanical Operated Internal Expanding			
Auxiliary		Exhaust Brake			
STEERING					
Steering System		Power Assist, Recirculating Ball Type			
Min. Turning Radius	m	5.1	7.3	5.6	7.3
ELECTRICAL					
Battery		95D31L x 1		80D26L x 2	
Alternator		12V-60A		24V-90A	
OTHER SAFETY					
Safety		Supplemental Restraint System (SRS) with Pre-Tensioner Seatbelt			
		Anti-Slip Regulator (ASR) with On/Off Function			
		Cab Tilt Warning			
Security		Central Locking with Remote Keyless Entry		Central Locking with Remote Keyless Entry & Immobiliser	
DIMENSION					
Overall Length	mm	4,730	6,025	4,730	6,025
Overall Width	mm	1,815			
Overall Height	mm	2,172	2,175	2,172	2,175
Wheelbase	mm	2,475	3,345	2,475	3,345
Front Overhang	mm	1,110			
Rear Overhang	mm	1,145	1,570	1,145	1,570
Front Tread	mm	1,475			
Rear Tread	mm	1,395		1,445	
Cab to Axle Center	mm	2,022	2,892	2,022	2,892

ISUZU

ISUZU MALAYSIA SDN BHD 200401026438 (664846-H)


501D, LEVEL 5, TOWER D, UPTOWN 5, NO.5, JALAN SS21/39,
DAMANSARA UPTOWN, 47400 PETALING JAYA, SELANGOR DARUL EHSAN.
GENERAL LINE: 03-7723 9777 FAX: 03-7723 9779
HOTLINE: 1-300-88-1133 www.isuzu.net.my

 [IsuzuTrucksMalaysia](#)  [IsuzuTrucksMalaysia](#)  [www.isuzu.net.my](#)

ISUZU SERVICE CENTRE SDN BHD 201601034731 (1205672-X)

LOT 730, JALAN SG. RASAU, SECTION 16,
40200 SHAH ALAM, SELANGOR DARUL EHSAN.
PHONE: 03-5513 0518
FAX: 03-5512 7550

TESTED AND PROVEN POWERTRAIN



NLR PRO

4JJ1-TCC


Displacement: 2,999cc

Max. Output (Gross): 77kW (105ps) @ 3,200rpm

Max. Torque: 230Nm @ 1,400 - 3,400rpm

105PS
Max Power

230Nm
Flat Torque



NMR 125

4JJ1-TC

Displacement: 2,999cc



Max. Output (Gross): 91kW (125ps) @ 2,600rpm

Max. Torque: 354Nm @ 1,500rpm

125PS
Max Power

354Nm
Flat Torque

CLASS-LEADING SAFETY AND LONG TERM COST SAVINGS



ASR traction control helps prevent wheelspins and improves vehicle stability when driving on slippery roads.

EBD is a function that uses the ABS to distribute braking force between the front and rear wheels to compensate for changes in the load conditions or any shift of load due to acceleration/deceleration, thus preventing premature locking of the rear wheels.



*SRS airbag system and seat belt with pretensioner are activated in the event of a frontal collision, mitigating impact to the head and chest.

*Applicable for driver only.

Brand New Feature - USB Port



Cabin Tilt Warning & Buzzer for driver safety warning



LED Headlight to provide better visibility



Gross Vehicle Weight (GVW) from 4.8T increased to 5.1T

Dealer's information

ISUZU
GENUINE PARTS

ISUZU
BEST VALUE PARTS